

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 2002-026664

(43)Date of publication of application : 25.01.2002

(51)Int.Cl.

H03F 1/26

H03F 3/68

(21)Application number : 2000-208622

(71)Applicant : TOSHIBA MICROELECTRONICS
CORP
TOSHIBA CORP

(22)Date of filing : 10.07.2000


(72)Inventor : HASEGAWA KENJI

(54) AMPLIFIER CIRCUIT

(57)Abstract:

PROBLEM TO BE SOLVED: To provide such amplifier circuits adopting a configuration of a plurality of stages having off-leak current interruption transistors (TRs) that input sensitivity is enhanced by noise prevention and a signal amplification characteristic is improved by suppressing a deviation in a circuit threshold value among the amplifier circuits.

SOLUTION: The amplifier circuits of the invention are connected between a signal input node and a signal output node in cascade and receive a power supply level at respective terminals, provided with output circuits, with a 1st switching element that is connected between the other respective terminals of the amplifier circuits of a plurality of the stages connected in common and a ground node and has a threshold value higher than switching elements being components of the amplifier circuits, and with a 2nd switching element that is connected between the other respective terminals of the output circuits and a ground node and has a threshold value higher than switching element being components of the output circuits.



LEGAL STATUS

[Date of request for examination]

30.01.2003

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]